


INTERCOM (XLR 5P, Female)



- EXT VIEW -
(0 dBu = 0.775 Vrms)

| No. | Signal | Specifications |
|-----|---------------------|--|
| 1 | INTERCOM MIC IN (Y) | -20 dBu (CARBON UNBALANCE) |
| 2 | INTERCOM MIC IN (X) | -40 dBu (ECM, UNBALANCE) -60 dBu (DYNAMIC, BALANCE/UNBALANCE) |
| 3 | GND | GND for INTERCOM |
| 4 | INTERCOM L OUT | 8 dBu (VR Max, 250 Ω Load) |
| 5 | INTERCOM R OUT | 8 dBu (VR Max, 250 Ω Load) |


LAN (8P, RJ-45, 10Base-T/100Base-TX)



- EXT VIEW -

| No. | Signal | Specifications |
|-----|--------|----------------------|
| 1 | TX (+) | Transmitted Data (+) |
| 2 | TX (-) | Transmitted Data (-) |
| 3 | RX (+) | Received Data (+) |
| 4 | NC | No connection |
| 5 | NC | No connection |
| 6 | RX (-) | Received Data (-) |
| 7 | NC | No connection |
| 8 | NC | No connection |

INTERCOM/TALLY/PGM (D-sub 25P, Female)




- EXT VIEW -
(0 dBu = 0.775 Vrms)

| No. | Signal | Specifications |
|-----|-----------------------|---|
| 1 | ENG (R) (X) OUT | ENG SYSTEM RECEIVE 0 dBu BALANCED |
| 2 | ENG (R) (Y) OUT | |
| 3 | ENG (G) | GND for ENG |
| 4 | ENG (T) (X) IN | ENG SYSTEM TALK 0 dBu BALANCED |
| 5 | ENG (T) (Y) IN | |
| 6 | PGM1 (X) IN | -20 dBu/0 dBu/+ 4 dBu (Selectable with CCU Menu) |
| 7 | PGM1 (Y) IN | |
| 8 | PGM1 (G) IN | |
| 9 | GND | GND for AUX |
| 10 | AUX3 | |
| 11 | R TALLY (X) IN | ON:24 Vdc, TTL (H), SHORT OFF:0 Vdc, TTL (L), OPEN |
| 12 | R TALLY (Y) IN | |
| 13 | GND | CHASSIS GND |
| 14 | PROD (R) (X) OUT | PROD SYSTEM RECEIVE 0 dBu BALANCED |
| 15 | PROD (R) (Y) OUT | |
| 16 | PROD (G) | GND for PROD |
| 17 | PROD (T) (X) IN | PROD SYSTEM TALK 0 dBu BALANCED |
| 18 | PROD (T) (Y) IN | |
| 19 | PGM2 (X) IN | -20 dBu/0 dBu/+ 4 dBu (Selectable with CCU Menu) |
| 20 | PGM2 (Y) IN | |
| 21 | PGM2 (G) IN | |
| 22 | EML* PIX/WF OUTPUT | Active:GND THROUGH (OFF):OPEN |
| 23 | EML Enable | Enable:GND Normal (Disable) :OPEN |
| 24 | G TALLY (X) IN | ON:24 Vdc, TTL (H), SHORT OFF:0 Vdc, TTL (L), OPEN |
| 25 | G TALLY (Y) IN | |

※: Easy Monitor Link function

MIC OUT 1, 2 (XLR 3P, Male)



- EXT VIEW -
(0 dBu = 0.775 Vrms)

| No. | Signal | Specifications |
|-----|-------------|--|
| 1 | MIC OUT (G) | 0 dBu/- 20 dBu (Selectable with CCU Menu) |
| 2 | MIC OUT (X) | |
| 3 | MIC OUT (Y) | |